



# WXL SERIES

**WARTHOG BEST CNC ROUTER "WXL SERIES"**  
**Standard Features**

- \*ALL STEEL 4"x 4" ONE PIECE WELDED FRAME
- \*HEAVY DUTY GANTRY
- \*UNIT IS A TRUE DUAL DRIVE
- \*5HP HIGH FREQUENCY SPINDLE
- \*HIGH PERFORMANCE INDUSTRIAL APPLICATION
- \*AC SERVO AND DRIVES
- INDUSTRIAL CONTROLLER,
- \*2400 IPM POSITIONING SPEED
- \*LINEAR RAILS ALL AXIS
- \*RACK AND PINION DRIVE SYSTEM ON X AND Y AXES
- \*INDUSTRIAL ANTI BACKLASH CONTROL SYSTEM
- \*BALL SCREW DRIVE ON Z AXIS
- \*MDF TABLETOP
- \*AUTOMATIC Z HEIGHT TOUCH TOP
- \*REPEATABILITY +/- .001
- \*RESOLUTION .0004
- \*SPINDLE BOOT FOR A DUST COLLECTION
- \*OPERATIONAL MANUAL
- \*FULL 3D FILES PROCESSING CAPABILITY
- \*CONTROL PANEL MOUNTED TO TABLE FRAME
- CLAMP, COLLET AND WRENCH
- \*EASY ACCESS EMERGENCY STOP
- \*240VAC- 3PHASE UNIT

**SXL SERIES GENERAL SPECIFICATION**

MODEL NUMBER	203	404	408	410	508	510
CUTTING AREA	24 x 36	48 x 48	48 x 96	48 x 120	60 x 96	60 x 120
Z AXIS CLEARANCE	6	6	6	6	6	6
Z AXIS TRAVEL	6	6	6	6	6	6
OVERALL LENGTH	72	84	135	160	135	160
OVERALL WIDTH	38	62	62	62	74	74
OVERALL HEIGHT	72	72	72	72	72	72
WEIGHT	1250	1575	1950	2150	2175	2400



Address:

Phone:

Email:

Warthog CNC  
 8801 Consolidated Dr.  
 Soddy Daisy, TN 37379

ph: 423-451-7213  
 fax: 423-451-7214

lfrench@warthogcnc.net  
 sales@warthogcnc.net